## **Technical Datasheet QC-7400**

## QUICKLINE® HS Clearcoat



Description	<b>Quickline HS Clearcoat</b> , <b>QC-7400</b> , is a two component, high solids acrylic urethane clearcoat suitable for panel repairs and complete resprays.					
Products	Hardeners:	QC-7400 <i>Quickline</i> HS Clearcoat QH-4410 <i>Quickline</i> HS Fast Hardener (Up to 20°C) QH-4420 <i>Quickline</i> HS Standard Hardener (Up to 25°C) QH-4430 <i>Quickline</i> HS Slow Hardener (25 – 35°C)				
Surface Preparation	See Basecoat Technical Data Sheet – QBC.  Note:  - Maximum basecoat flash-off time before application of QC-7400 HS Clearcoat is 24 hours.  If left longer, scuff thoroughly and apply additional basecoat.  - Go over the basecoat surface with a suitable tack-rag immediately before application of QC-7400 HS Clearcoat.  QC-7400 HS Clearcoat is not recommended for use over Waterborne basecoats.					
Mixing			By volume:			
	Quickline HS Clearcoat QC-7400 Quickline HS Hardener QH-4410/4420/4430 Pot Life:			2 Parts 1 Part 3 - 4 Hours		
Application  >1	Conventional gun:  HVLP/Compliant gun:		ip 1.4 – 1.6mm, Aiı	pressure 50 psi (3.5 bar) at the gun pressure – refer to spraygun manufacturers		
Coats	2 coats (50 – 60 microns dry film)					
Flash Time	5 – 10 minutes between coats at 20°C					
Drying -	Air Dry at 20°C		Dust Free: Polish/Into Servio Handleable	ce	40-75 mins 16 hours (overnight) 5 - 6 hours	
	Force Dry:		Tape Free 50°C Polish/Into Servio		10 - 12 hours 25 - 30 minutes 2 hours after full cooling	

## **Process Notes**

Clean up equipment immediately after use, using *Quickline* MS Thinner or another suitable solvent. Dispose of waste in accordance with applicable regulations.

These products are for professional painting only, and are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps in order to ensure the suitability of the product for the intended purpose.

**QUICKLINE®**